

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY OF
TOWNSHIP 3 SOUTH, RANGE 6 WEST,

THE DEPENDENT RESURVEY OF THE EAST BOUNDARY,
AND A PORTION OF MINERAL SURVEY NO. 5615 OF
TOWNSHIP 2 SOUTH, RANGE 7 WEST,

THE DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,

AND THE SUBDIVISION OF SECTIONS 7, 18, 20, AND 29,

AND A PORTION OF MINERAL SURVEY Nos. 5615 AND 5621,

AND THE METES-AND-BOUNDS SURVEY OF PARCELS 1 AND 2,

IN

TOWNSHIP 2 SOUTH, RANGE 6 WEST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Daniel T. Gillins
Survey Technician

Under the Supervision of

Ronald K. Baugh
Supervisory Cadastral Surveyor

Under Special Instructions dated and approved **August 23, 2007**, which provided for the surveys included under Group Number **1052**, and Assignment Instructions dated **August 23, 2007**.

Survey Commenced, **September 10, 2007**
Survey Completed, **April 19, 2008**

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

S. 0°04.2' E., on the east boundary of section 13.

- 19.795 Point for the N 1/16 section corner of section 18 only, Township 2 South, Range 6 West, not monumented.
- 39.881 The 1/4 section corner of section 18 only, Township 2 South, Range 6 West, monumented with a G.L.O. iron post, 1 inch diameter, firmly set, 22 inches in the ground, broken at ground surface, with the remaining iron post with brass cap lying alongside, marked:

$\begin{array}{c} | \quad 1/4 \\ | \quad S \ 18 \\ 1914 \end{array}$

There is no record of this G.L.O. monument in the official record of the 1912-15 survey. This position is harmoniously related to existing original corners, has long been recognized as the corner, and is accepted as the original corner position. See note 1.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

$\begin{array}{c} T \ 2 \ S \\ R \ 7 \ W \ R \ 6 \ W \\ | \quad 1/4 \\ | \quad S \ 18 \\ 2007 \end{array}$

Deposit the 1912 iron post alongside the aluminum post.

Set a U-channel aluminum fence post along the north side of aluminum post.

Corner is located on a steep, north facing slope.

- 40.198 The 1/4 section corner of section 13 only, monumented with an iron post, 1 inch diameter, firmly set, 24 inches in the ground, broken at ground surface, with a mound of stone 3 ft. base, 1 1/2 ft. high, 2 links west, and the remaining iron post with brass cap lying alongside, marked:

$\begin{array}{c} 1/4 \ | \\ S \ 13 \ | \\ 1912 \end{array}$

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 2 S
R 7 W R 6 W
1/4 |
S 13 |
2007

Deposit the 1912 iron post alongside the aluminum post.

Set a U-channel aluminum fence post along the south side of aluminum post.

Corner is located on very steep, north facing slope.

S. 0°02.3' E., beginning new measurement.

- 39.571** The closing corner of sections 18 and 19, Township 2 South, Range 6 West, monumented with an iron post, 2 inches diameter, firmly set, 18 inches in the ground, broken at ground surface, with remaining iron post with brass cap lying alongside, marked as described in the official record of the 1912-15 survey.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

T 2 S
T 7 S R 6 W
| C S 18
S 13 | C S 19
2007

Deposit the 1912 iron post alongside the aluminum post.

Corner is located on a steep, east facing slope.

- 39.918** The corner of sections 13 and 24 only, monumented with an iron post, 3 inches diameter, set in a mound of stone, 3 ft. base, 24 inches high, to top of brass cap marked as described in the official record of the 1912-15 survey.

Corner is located on steep, east facing slope.

S. 0°03.1' W., on the east boundary of section 24.

- 39.816** The 1/4 section corner of section 19 only, Township 2 South, Range 6 West, bears West, 0.030 chains distance, monumented with a G.L.O. iron post, 1 inch diameter, firmly set, projecting 12 inches above the ground, with a mound of stone, 2 ft. base, 1 1/2 ft. high, 3 links west, and a brass cap marked:

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

1/4 |
 S 19
 |
 1912

There is no record of this G.L.O. monument in the official record of the 1912-15 survey. This position is harmoniously related to existing original corners, has long been recognized as the corner, and is accepted as the original corner position. See note 1.

- 40.143** The 1/4 section corner of section 24 only, monumented with an iron post, 1 inch diameter, firmly set, projecting 14 inches above the ground with brass cap marked:

1/4 |
S 24 |
 |
 1914

Corner is located on steep, north facing slope.

S. 0°01.2' W., beginning new measurement.

- 16.351** Intersect line 6 - 7 of Mineral Survey No. 5615.

Set an aluminum post, 15 inches long, 2 1/2 inches diameter, 2 inches in the ground over an X chiseled in solid rock, in a mound of stone, 3 ft. base to top of aluminum cap marked:

IP
S 24 ———— S 19
 |
 MS 5615
 |
 2008

- 36.375** Intersect line 4 - 5 of Mineral Survey No. 5615, point for angle point 2 of parcel 1, hereinafter described.
- 39.752** True point for the closing corner of sections 19 and 30, Township 2 South, Range 6 West, hereinafter described.
- 40.107** The corner of sections 24 and 25 only, monumented with an iron post, 3 inches diameter, firmly set, 20 inches in the ground, broken at ground surface, with remaining iron post with brass cap lying alongside, marked as described in the official record of the 1912-15 survey.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, in a mound of stone, 3 ft. base to top of aluminum cap marked:

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 2 S	
R 7 W	R 6 W
S 24	S 30
S 25	

2007

Deposit the 1912 iron post alongside the aluminum post.

Set a steel fence post along the southwest side of aluminum post.

Corner is located on east facing slope next to a cedar stump.

S. 0°03.5' W., along the east boundary of section 25.

- 39.599 The 1/4 section corner of section 30 only, Township 2 South, Range 6 West, monumented with a G.L.O. iron post, 1 inch diameter, firmly set, 12 inches in the ground, broken at ground surface, with remaining iron post with brass cap lying alongside, marked:

1/4	S 30

1914

There is no record of this G.L.O. monument in the official record of the 1912-15 survey. This position is harmoniously related to existing original corners, has long been recognized as the corner, and is accepted as the original corner position. See note 1.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, in a mound of stone, 3 ft. base to top of aluminum cap marked:

T 2 S	
R 7 W	R 6 W
	1/4
	S 30

2007

Deposit the 1914 iron post alongside the aluminum post.

Corner is located on a steep, southeast facing slope.

- 39.765 The 1/4 section corner of section 25 only, monumented with an iron post, 1 inch diameter, set 2 inches in the ground, broken at ground surface, with remaining iron post with brass cap lying alongside, marked:

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

1/4 |
S 25 |
1912

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with aluminum cap marked:

T 2 S
R 7 W R 6 W
1/4 |
S 25 |
2007

Deposit the 1912 iron post alongside the aluminum post.

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, west of corner.

S. 0°01.1' W., beginning new measurement.

- 40.239 The corner of sections 25, 30, 31, and 36, monumented with an iron post, 3 inches diameter, firmly set, 18 inches in the ground, broken at ground surface. Did not find the remaining iron post with brass cap.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T 2 S
R 7 W R 6 W
S 25 | S 30
S 36 | S 31
2007

Deposit the 1912 iron post alongside the aluminum post.

Set a steel fence post along the northwest side of aluminum post.

Corner is located under an east and west barbed wire fence and on the east edge of a northwest and southeast ATV road.

S. 0°01.1' W., between sections 31 and 36.

- 40.063 The 1/4 section corner of sections 31 and 36, monumented with an iron post, 1 inch diameter, firmly set, 18 inches in the ground, broken at ground surface, with remaining iron post with brass

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

cap lying alongside, marked as described in the official record of the 1912 survey.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, in a mound of stone, 3 ft. base to top of aluminum cap marked:

T 2 S
R 7 W R 6 W
1/4
S 36 | S 31
2007

Deposit the 1912 iron post inside aluminum post.

Set a steel fence post along the north side of aluminum post.

Corner is located 30 ft. north of drainage, drains northeast.

S. 0°02.2' W., beginning new measurement.

- 40.004 The closing corner of Township 2 South, Ranges 6 and 7 West, hereinbefore described.

Dependent Resurvey of a Portion of the Subdivisional Lines in
Township 2 South, Range 6 West, Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by J.R. Stewart
& R. Gentry in 1912-15

From the corner of sections 31 and 32 only, on the south boundary of the township, hereinbefore described.

N. 0°00.5' E., between sections 31 and 32.

- 40.085 The 1/4 section corner of sections 31 and 32, monumented with an iron post, 1 inch diameter, firmly set, in a mound of stone, 3 ft. base, 6 inches high, to top of loose brass cap marked as described in the official record of the 1912-15 survey; from which the remains of a north and south barbed wire fence bears west, 1 ft. distance.
-

N. 0°02.0' E., beginning new measurement.

- 40.145 The corner of sections 29, 30, 31, and 32, monumented with an iron post, 2 inches diameter, broken 2 inches above ground

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN
TOWNSHIP 2 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

surface. Did not find the remaining iron post with brass cap.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, in a mound of stone, 2 ft. base to top of aluminum cap marked:

T 2 S R 6 W

S 30	S 29
S 31	S 32

2007

Deposit the 1912 iron post inside aluminum post.

Set a steel fence post along the southwest side of aluminum post.

S. 89°46.9' W., between sections 30 and 31.

- 39.959 The 1/4 section corner of sections 30 and 31, monumented with an iron post, 1 inch diameter, firmly set, 25 inches in the ground, broken at ground surface, with remaining iron post, with brass cap lying alongside, marked as described in the official record of the 1912-15 survey.

This point will function as an angle point of sections 30 and 31.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with aluminum cap marked:

T 2 S R 6 W

S 30

1/4 —————

S 31

2007

Deposit the 1912 iron post inside aluminum post.

Set a steel fence post along the west side of aluminum post.

Corner is located 4 ft. north of the remains of an east and west barbed wire fence.

S. 89°24.4' W., beginning new measurement.

- 2.191 The corner of sections 25, 30, 31, and 36, on the east boundary of the township, hereinbefore described.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN
TOWNSHIP 2 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 29, 30, 31, and 32.

N. 0°00.7' W., between sections 29 and 30.

- 40.160 The 1/4 section corner of sections 29 and 30, monumented with an iron post, 1 inch diameter, firmly set, projecting 4 inches above the ground, with brass cap marked as described in the official record of the 1912-15 survey.

Corner is located on a west slope overlooking drainage to the west, drains southeast.

N. 0°01.8' E., beginning new measurement.

- 19.808 Point for angle point 1 of parcel 2.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

	PL-2
	AP1
S 30	S 29
2007	

Set a steel fence post along the north side of aluminum post.

Corner is located on southeast facing slope.

- 20.077 Point for the N 1/16 section corner of sections 29 and 30.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground with aluminum cap marked:

N 1/16	
S 30	S 29
2007	

Set a steel fence post along the north side of aluminum post.

- 40.154 The corner of sections 19, 20, 29, and 30, monumented with an iron post, 2 inches diameter, firmly set, projecting 14 inches above the ground, with brass cap marked as described in the official record of the 1912-15 survey, with a mound of stone, 4 ft. base, 2 ft. high, west of corner.

From the 1/4 section corner of sections 20 and 29, perpetuated and recorded by Joseph Don Richardson, Registered Land Surveyor No. 4265, in 2004, remonumented with an iron pipe, 2 inches diameter, firmly set, in a mound of stone, 3 ft. base, 1 ft. high to top of brass cap, 3 inches diameter marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN
TOWNSHIP 2 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

TOOELE COUNTY SURVEYOR

T 2 S R 6 W

1/4 S 20

S 29

2004

Mr. Richardson determined the corner position at the remains of a rusted and broken 1914 iron post, 1 inch diameter, set in a mound of stone as per the Tooele County Section Corner Ties sheet on file with the Tooele County Surveyor's Office. This point is accepted as a careful and faithful perpetuation of the original corner position.

Corner is located at the intersection of barbed wire fences extending north and east.

N. 89°59.3' W., between sections 20 and 29.

36.878 The corner of sections 19, 20, 29, and 30.

S. 89°45.1' W., between sections 19 and 30.

19.916 Point for the E 1/16 section corner of sections 19 and 30.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground to bedrock, in a mound of stone, 3 ft. base to top of aluminum cap marked:

	S 19
E 1/16	<hr/>
	S 30
	2007

Set a steel fence post along the northeast side of aluminum post.

Corner is located on an east facing slope.

39.832 The 1/4 section corner of sections 19 and 30, monumented with an iron post, 1 inch diameter, firmly set, 21 inches in the ground, broken at ground surface, with remaining iron post with brass cap lying alongside, marked as described in the official record of the 1912-15 survey.

This point will function as an angle point of sections 19 and 30.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, in a mound of stone, 3 ft. base to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN
TOWNSHIP 2 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 2 S R 6 W
S 19
1/4 —————
S 30
2007

Deposit the 1912 iron post alongside the aluminum post.

Set a steel fence post along the south side of aluminum post.

Corner is located on an east facing slope, approximately 100 ft. west of an old north and south fence.

N. 88°58.0' W., beginning new measurement.

- 2.244 The monumented closing corner of sections 19 and 30, monumented with an iron post, 2 inches diameter, firmly set, projecting 6 inches above the ground, with brass cap marked as described in the official record of the 1912-15 survey.

This corner will now function as an amended monument; no marks were added to the brass cap.

- 2.267 The true point for the closing corner of sections 19 and 30, at the intersection with the east boundary of Township 2 South, Range 7 West.

From the corner of sections 19, 20, 29, and 30.

N. 0°01.5' E., between sections 19 and 20.

- 4.661 Intersect the north boundary of parcel 1, hereinafter described.

- 40.021 The 1/4 section corner of sections 19 and 20, monumented with an iron post, 1 inch diameter, firmly set in a mound of stone, 5 ft. base, 18 inches high to top of brass cap marked as described in the official record of the 1912-15 survey.

From the 1/4 section corner of section 18 only, monumented with an iron post, 1 inch diameter, firmly set in mound of stone, 4 ft. base, 12 inches high to top of brass cap marked as described in the official record of the 1912-15 survey.

Corner is located on a south facing slope, 11 ft. north of drainage, course east.

N. 0°04.0' E., on the east boundary of section 18.

- 0.402 The 1/4 section corner of section 17 only, bears West, 0.025 chains distance, monumented with an iron post, 1 inch diameter, firmly set in mound of stone, 4 ft. base, 6 inches high to top of brass cap marked as described in the official record of the 1912-

INDEX DIAGRAM

Township 2 South, Range 6 West

4 6	5	4	3	2	1
6 7 18	19 8	9	10	11	12
8 18	17 17	16	15	14	13
9 19 16	17 20 15	21	22	23	24
11 30 14	15 29	28	27	26	25
12 31 3	13 32	33	34	35	36

The Subdivision of Section 7.....	Page 20
The Subdivision of Section 18.....	Page 21
The Subdivision of Section 20.....	Page 22
The Subdivision of Section 29.....	Page 22
Mineral Survey No. 5615.....	Page 23
Mineral Survey No. 5621.....	Page 26
Parcel 1.....	Page 27
Parcel 2.....	Page 30

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN
TOWNSHIP 2 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

15 survey.

- 20.019 Point for the N 1/16 section corner of section 18 only, not monumented.
- 40.038 The corner of sections 7 and 18 only, monumented with an iron post, 2 inches diameter, firmly set, projecting 18 inches above the ground with brass cap marked as described in the official record of the 1912-15 survey, with a mound of stone, 3 ft. base, 2 ft. high, 3 ft. west, and a steel fence post 2 ft. south of corner.

N. 89°58.9' W., between sections 7 and 18.

- 6.580 Intersect line 3 - 4 of Mineral Survey No. 5621

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, in a mound of stone, 3 ft. base to top of aluminum cap marked:

```

      T 2 S R 6 W
        S 7
        |
  -----
        |
        S 18
        2008
      MS 5621
  
```

Set a steel fence post along the northeast side of aluminum post.

Corner is located on fill slope of a northeast and southwest ancient mining road.

- 20.037 Point for the E 1/16 section corner of sections 7 and 18.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a mound of stone, 3 ft. base to top of aluminum cap marked:

```

              S 7
  E 1/16  -----
              S 18
              2008
  
```

Set a steel fence post alongside aluminum post.

Corner is located on very steep, east facing slope.

- 40.074 Point for the 1/4 section corner of sections 7 and 18, at proportionate distance. Found the entire 1914 iron post, 1 inch diameter, lying out of the ground, down the hill, with brass cap marked as described in the official record of the 1912-15 survey, nearly broken at the base.

This point will function as an angle point of sections 7 and 18.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN
TOWNSHIP 2 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 8 inches in the ground, in a mound of a stone, 4 ft. base to top of aluminum cap marked:

T 2 S R 6 W
S 7
1/4 —————
S 18
2008

Deposit the 1912 iron post alongside the aluminum post.

Corner is located on steep, west facing slope.

- 42.148** The closing corner of sections 7 and 18, at intersection with the east boundary of Township 2 South, Range 7 West, hereinbefore described.

From the corner of sections 7 and 18 only.

N. 0°01.4' W., on the east boundary of section 7.

- 0.668** The closing corner of sections 8 and 17, monumented with an iron post, 2 inches diameter, firmly set, projecting 14 inches above the ground, with brass cap marked as described in the official record of the 1912-15 survey, with a mound of stone, 3 ft. base, 1 1/2 ft. high, 3 ft. east and a steel fence post 1 1/2 ft north of corner.

- 1.648** Intersect line 4 - 5 of Mineral Survey No. 5621.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a mound of stone, 2 1/2 ft. base to top of aluminum cap marked:

S7 ——— S8
MS 5621
2008

Set a steel fence post along the south side of aluminum post.

- 19.980** Point for the S 1/16 section corner of section 7 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with aluminum cap marked:

S 1/16
S 7
2008

Set a steel fence post along the west side of aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES IN
TOWNSHIP 2 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 39.960** The 1/4 section corner of section 7 only, monumented with an iron post, 1 inch diameter, firmly set, projecting 10 inches above the ground with brass cap marked as described in the official record of the 1912-15 survey.

Raise a mound of stone, 3 ft. base, 1 ft. high, 2 links west of corner.

The Subdivision of Section 7 in
Township 2 South, Range 6 West, Salt Lake Meridian, Utah

From the 1/4 section corner of section 7 only.

N. 89°40.2' W., on the E-W center line of section 7.

- 20.057** Point for the center E 1/16 section corner of section 7, not monumented.

- 42.175** The 1/4 section corner of section 7 only, on the east boundary of Township 2 South, Range 7 West, hereinbefore described.

From the E 1/16 section corner of sections 7 and 18.

N. 0°03.3' W., on the N-S center line of the SE 1/4 of section 7.

- 20.035** Point for the SE 1/16 section corner of section 7, at intersection with the E-W center line of the SE 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

SE 1/16 S 7

2008

Set a steel fence post along the west side aluminum post.

Corner is located under an east and west electric fence.

- 40.070** The point for the center E 1/16 section corner of section 7.

From the S 1/16 section corner of section 7 only.

N. 89°49.6' W., on the E-W center line of the SE 1/4 of section 7.

- 20.047** The SE 1/16 section corner of section 7.

- 42.161** The point for the S 1/16 section corner of section 7 only, on the east boundary of Township 2 South, Range 7 West, hereinbefore described.

THE SUBDIVISION OF SECTION 18 IN
TOWNSHIP 2 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 18 in
Township 2 South, Range 6 West, Salt Lake Meridian, Utah

From the 1/4 section corner of section 18 only.

S. 89°50.2' W., on the E-W center line of section 18.

19.980 Point for the center E 1/16 section corner of section 18, not monumented.

42.057 The 1/4 section corner of section 18 only, on the east boundary of Township 2 South, Range 7 West, hereinbefore described.

From the point for the center E 1/16 section corner of section 18.

N. 0°01.1' W., on the N-S center line of the NE 1/4 of section 18.

20.051 Point for the NE 1/16 section corner of section 18, at intersection with the E-W center line of the NE 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 4 inches in the ground to bedrock, in a mound of stone, 4 ft. base to top of aluminum cap marked:

NE 1/16 S 18

2008

Corner is located on a rocky, southeast facing slope.

40.102 The E 1/16 section corner of sections 7 and 18.

From the point for the N 1/16 section corner of section 18 only.

S. 89°55.6' W., on the E-W center line of the NE 1/4 of section 18.

6.583 Intersect line 3 - 4 of Mineral Survey No. 5621.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a mound of stone, 3 ft. base to top of aluminum cap marked:

T 2 S R 6 W
S 18 ——— | MS 5621
2008

Set a steel fence post along the northwest side of aluminum post.

THE SUBDIVISION OF SECTION 18 IN
TOWNSHIP 2 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located on steep east slope.

- 20.009 The NE 1/16 section corner of section 18.
- 42.103 The point for the N 1/16 section corner of section 18 only, on the east boundary of Township 2 South, Range 7 West, hereinbefore described.

The Subdivision of Section 20 in
Township 2 South, Range 6 West, Salt Lake Meridian, Utah

From the 1/4 section corner of sections 20 and 29.

N. 1°05.3' W., on the N-S center line of section 20.

- 4.680 Angle point 5 of parcel 1, hereinafter described.
- 81.620 The 1/4 section corner of section 20 only, monumented with an iron post, 1 inch diameter, firmly set, projecting 12 inches above the ground, with brass cap marked as described in the official record of the 1912-15 survey.

Corner is located at the toe of an east-northeast facing slope, under an old north and south barbed wire fence.

The Subdivision of Section 29 in
Township 2 South, Range 6 West, Salt Lake Meridian, Utah

From the 1/4 section corner of sections 29 and 32, monumented with an iron post, 1 inch diameter, projecting 10 inches above the ground, with brass cap marked as described in the official record of the 1912-15 survey.

The corner is located 30 ft. north of the north edge of an east and west dirt road, and 16 ft. south of an east and west barbed wire fence.

N. 1°02.0' W., on the N-S center line of section 29.

- 40.173 Point for the center 1/4 section corner of section 29 at the intersection with the E-W center line of section, not monumented.
- 59.985 Point for angle point 2 of parcel 2.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T 2 S R 6 W
C
PL-2 |
AP2 | S 29
C
2007

THE SUBDIVISION OF SECTION 29 IN
TOWNSHIP 2 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post along the northwest side of aluminum post.

60.254 Point for the center N 1/16 section corner of section 29.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground to bedrock, in a mound of stone, 3 ft. base to top of aluminum cap marked:

C
|
N 1/16 | S 29
|
C
2007

Set a U-channel aluminum post along the west side of aluminum post.

80.335 The 1/4 section corner of sections 20 and 29.

From the 1/4 section corner of sections 28 and 29, monumented with an iron post, 1 inch diameter, firmly set, projecting 16 inches above the ground, with brass cap marked as described in the official record of the 1912-15 resurvey, with a scattered mound of stone west, and a steel fence post 1 ft. northwest of corner.

Corner is located under a north and south barbed wire fence.

N. 89°58.9' W., on the E-W center line of section 29.

40.007 The point for the center 1/4 section corner of section 29.

77.634 The 1/4 section corner of sections 29 and 30.

From the center N 1/16 section corner of section 29.

N. 89°59.2' W., on the E-W center line of the NW 1/4 of section 29.

37.253 The N 1/16 section corner of sections 29 and 30.

Dependent Resurvey of a Portion of the Black Shale No. 1 Placer,
Mineral Survey No. 5615, Utah

Reestablishment of the Survey Executed by H. Fitzhugh in 1906

From Corner No. 3 of Mineral Survey No. 5615, perpetuated and recorded by Joseph Don Richardson, Registered Land Surveyor No. 4265, in 2004, remonumented with a 5/8 inch diameter rebar with yellow plastic cap marked "RICHARDSON SURVEYING INC PLS 4265", firmly set, in a mound of stone and concrete, 3 ft. base, 1 1/2

DEPENDENT RESURVEY OF A PORTION OF THE BLACK SHALE NO. 1 PLACER,
MINERAL SURVEY NO. 5615, UTAH

CHAINS

ft. high.

Note: Mr. Richardson determined the corner position at the center of a mound of stone (which is believed to be the best available evidence of the original corner position) as per his ALTA/ACSM Land Title Survey plat on file with the Tooele County Surveyor's Office, No. 04-0026-01. This point is accepted as a careful and faithful perpetuation of the original corner position.

S. $0^{\circ}20.1'$ W., on line 3 - 4 of Mineral Survey No. 5615.

18.647 Angle point 4 of parcel 1, hereinafter described.

20.133 Corner No. 4 of Mineral Survey No. 5615, perpetuated and recorded by Joseph Don Richardson, Registered Land Surveyor No. 4265, in 2004, remonumented with a 5/8 inch diameter rebar with yellow plastic cap marked "RICHARDSON SURVEYING INC PLS 4265", firmly set, in a mound of stone, 3 ft. base, 1 1/2 ft. high, with the remains of a pine post on top.

Note: Mr. Richardson determined the corner position at the remains of a 4 inch square pine post set in a mound of stone as per his ALTA/ACSM Land Title Survey plat on file with the Tooele County Surveyor's Office, No. 04-0026-01. This point is accepted as a careful and faithful perpetuation of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, in a mound of stone, 3 ft. base to top of aluminum cap marked:

T 2 S R 6 W	
MS	
5615	
COR 4	S 19

2007

Deposit the rebar inside aluminum post.

Set a steel fence post along the north side of aluminum post.

Corner is located on northeast facing slope, 52 ft. south of the bottom of a canyon, drains southeast.

Thence, N. $89^{\circ}42.1'$ W., on line 4 - 5 of Mineral Survey No. 5615.

15.555 Intersect the east boundary of Township 2 South, Range 7 West, the point for angle point 2 of parcel 1, hereinafter described.

19.977 Point for Corner No. 5 of Mineral Survey No. 5615, determined by grant boundary adjustment. There is no remaining evidence of the

DEPENDENT RESURVEY OF A PORTION OF THE BLACK SHALE NO. 1 PLACER,
MINERAL SURVEY NO. 5615, UTAH

CHAINS

original corner.

Set an aluminum post, 20 inches long, 2 1/2 inches diameter, 10 inches in the ground, in a mound of stone, 3 ft. base, 2 ft. high, with aluminum cap marked:

T 2 S R 7 W	
S 24	MS 5615
	COR 5

2007

Set a steel fence post along the north side of aluminum post.

Corner is located on a steep, northeast facing slope surrounded by cedar trees.

Thence, N. 0°17.9' E., on line 5 - 6 of Mineral Survey No. 5615.

19.977 Corner No. 6 of Mineral Survey No. 5615, determined at record distances from the 1906 bearing trees:

A cedar, 9 inches diameter, bears S. 3°17' W., 17.5 ft.
distance, with scribe marks 6-5615 BT on an open blaze.
(Record: S. 5°30' E.)

A cedar, 14 inches diameter, bears N. 42°12' W., 31.5 ft.
distance, with scribe marks 6-5615 BT on an open blaze.
(Record: N. 37°15' W.)

Found the 1906 cedar post, 4 inches square, 4 ft. long, with scribe marks 6 X 5615, lying out of ground, alongside the corner point.

At the corner point

Set an aluminum post, 20 inches long, 2 1/2 inches diameter, 14 inches in the ground to bedrock, in a mound of stone, 3 ft. base to top of aluminum cap marked:

T 2 S R 7 W	
S 24	COR 6
	MS 5615

2007

Re-set the 1906 cedar post alongside aluminum post.

Corner is located on a steep, east facing slope.

Thence, N. 89°41.0' E., on line 6 - 7 of Mineral Survey No. 5615.

DEPENDENT RESURVEY OF A PORTION OF THE BLACK SHALE NO. 1 PLACER,
MINERAL SURVEY NO. 5615, UTAH

CHAINS

4.325 Intersect the east boundary of Township 2 South, Range 7 West, hereinbefore described.

10.011 Corner No. 7 of Mineral Survey No. 5615, determined at the center of a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high. There is no remaining evidence of the 1906 pine post.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, in a mound of stone, 2 1/2 ft. base to top of aluminum cap marked:

T 2 S R 6 W	
S 19	
	COR 7
	MS 5615
	2007

Corner is located on a steep, north facing slope.

Dependent Resurvey of a Portion of the Quarry Anton Placer,
Mineral Survey No. 5621, Utah

Reestablishment of the Survey Executed by H. Fitzhugh in 1906

From corner No. 3 of Mineral Survey No. 5621, determined at the center of a mound of stone, 3 ft. base, 2 ft. high, with a survey lathe alongside. There is no remaining evidence of the 1906 cedar post.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, in a mound of stone, 3 ft. base, 12 inches high, with aluminum cap marked:

T 2 S R 6 W	
S 18	
	MS 5621
	COR 3
	2007

Set a steel fence post along the north side of aluminum post.

N. 0°04.3' E., on line 3 - 4 of Mineral Survey No. 5621.

18.224 Intersect the E-W center line of the NE 1/4 of section 18, hereinbefore described.

38.253 Intersect the line between sections 7 and 18, hereinbefore described.

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY No. 5621
IN TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 39.906 Corner No. 4 of Mineral Survey No. 5621, determined at a 4 inch square hole in the center of a mound of stone, 3 ft. base, 1 1/2 ft. high. There is no remaining evidence of the 1906 cedar post - it may have burned in recent fire.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a mound of stone, 3 ft. base to top of aluminum cap marked:

T 2 S R 6 W
S 7
COR 4
MS 5621
2008

Thence, S. 89°56.2' E., on line 4 - 5 of Mineral Survey No. 5621.

- 6.577 Intersect the line between sections 7 and 8, hereinbefore described.
- 19.880 Point for corner No. 5 of Mineral Survey No. 5621, determined by grant boundary adjustment, there is no remaining evidence of the original corner. Point falls in east and west dirt road, not monumented.

From this point, corner No. 6 of Mineral Survey No. 5621, monumented with a 1/2 inch diameter rebar set in a mound of stone, 3 ft. base, 1 1/2 ft. high, bears S. 0°03.8' W., 39.761 chains distance. There is no remaining evidence of the 1906 cedar post. This point was utilized as the corner position by Joseph Don Richardson, Registered Land Surveyor No. 4265, in 2004, as per his ALTA/ACSM Land Title Survey plat on file with the Tooele County Surveyor's Office, No. 04-0026-01, is harmoniously related to existing original mineral survey corners, and is accepted as the best available evidence of the original corner position.

The Metes and Bounds Survey of Parcel 1 in
Township 2 South, Range 6 West, Salt Lake Meridian, Utah

The Metes and Bounds Survey is based upon Parcel 1 of the Warranty Deed filed with the Tooele County recorder's office, dated November 30, 1995, book 409, pages 435-436; Stansbury Investments Associates, Grantor and the United States Of America, Grantee.

Note: Parcel 1 shall hereby consist of lots 13 and 14 of section 19, and lots 8 and 9 of section 20, as depicted on the survey

TOWNSHIP 2 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH.

The following field notes are those of the dependent resurveys of a portion of the north boundary of T. 3 S., R. 6 W., the dependent resurvey of the east boundary, and a portion of mineral survey no. 5615 of T. 2 S., R. 7 W., the dependent resurvey of a portion of the subdivisional lines, and the subdivision of sections 7, 18, 20, and 29, and a portion of mineral survey nos. 5615 and 5621, and the metes-and-bounds survey of parcels 1 and 2, in T. 2 S., R. 6 W., Salt Lake Meridian, Utah.

HISTORY OF SURVEYS

Surveyed by		Retr. Or Resurveyed by	
SOUTH BOUNDARY			
Portion	C.L. Craig	1856	
Portion	J.R. Stewart & C.L. Heist	1912	
EAST BOUNDARY			
All	C.L. Craig	1856	
WEST BOUNDARY			
All	C.L. Heist	1912	
NORTH BOUNDARY			
Portion	C.L. Craig	1856	
Portion	C.L. Heist	1912	C.L. Heist 1912
Portion		J.R. Stewart & F.D. Dalton	1913
SUBDIVISION			
Portion	C.L. Craig	1856	
Portion	J.R. Stewart & R. Gentry	1912	J.R. Stewart & R. Gentry 1912
		-15	-15
PRIVATE SURVEY			

J.D. Richardson (R.L.S. 4265) 2004

MINERAL SURVEYS

No. 5615	H. Fitzhugh	1906
No. 5621	H. Fitzhugh	1906

The Metes and Bounds Survey is based upon Parcel 1 and 2 of the Warranty Deed filed with the Tooele County recorder's office, dated November 30, 1995, book 409, pages 435-436; Stansbury Investments Associates, Grantor and the United States Of America, Grantee.

Note: Parcel 1 shall hereby consist of lots 13 and 14 of section 19, and lots 8 and 9 of section 20, as depicted on the survey plat.

Note: Parcel 2 shall hereby consist of lots 1, 5, and 6, and the NE 1/4 of the NW 1/4 of section 29, as depicted on the survey plat.

THE METES AND BOUNDS SURVEY OF PARCEL 1 IN
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

plat.

From the true point for the closing corner of sections 19 and 30, hereinbefore described. This point shall now also function as angle point 1 of parcel 1.

N. 0°01.2' E., along the east boundary of section 24, T. 2 S., R. 7 W.

- 3.377** Intersect line 4 - 5 of Mineral Survey No. 5615, the point for angle point 2 of parcel 1.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

```

      T 2 S
    T 7 S R 6 W
      MS 5615
S 24 ———— S19
      |
      | AP2
      | PL-1
      |
      2007
  
```

Set a steel fence post along the west side of aluminum post.

Corner is located on an east facing slope, surrounded by cedar trees.

Thence, **S. 89°42.1' E.**, along line 5 - 4 of Mineral Survey No. 5615.

- 15.555** Corner No. 4 of Mineral Survey No. 5615, hereinbefore described. This point shall now also function as angle point 3 of parcel 1.

Thence, **N. 0°20.1' E.**, along line 4 - 3 of Mineral Survey No. 5615.

- 1.486** Angle point 4 of parcel 1, monumented and recorded in 2004 by Joseph Don Richardson, Registered Land Surveyor No. 4265, with a 5/8 inch diameter rebar, firmly set, projecting 9 inches above the ground, with yellow plastic cap marked "RICHARDSON SURVEYING INC PLS 4265", as described in ALTA/ACSM Land Title Survey plat filed with the Tooele County Surveyor's Office, No. 04-0026-001. Accepted as a careful and faithful determination of the corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

THE METES AND BOUNDS SURVEY OF PARCEL 1 IN
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

MS 5615	S 19
	AP 4
	PL-1
	2007

Deposit the rebar alongside aluminum post.

Corner is located on south slope, 52 ft. north of the bottom of a canyon, drains southeast.

Thence, N. 89°58.8' E.

26.535 Intersect the section line between sections 19 and 20.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

T 2 S R 6 W	
S 19	S 20
PL-1	
2007	

Set a steel fence post along the north side of aluminum post.

Corner is located on a gentle, southeast facing slope.

63.321 Angle point 5 of parcel 1, at the intersection with the N-S center line of section 20, monumented and recorded in 2004 by Joseph Don Richardson, Registered Land Surveyor No. 4265, with a 5/8 inch diameter rebar, firmly set, projecting 4 inches above the ground, with yellow plastic cap marked "RICHARDSON SURVEYING INC PLS 4265", as described in ALTA/ACSM Land Title Survey plat filed with the Tooele County Surveyor's Office, No. 04-0026-01. Accepted as a careful and faithful determination of the corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

T 2 S R 6 W	
	C
	S 20
AP5	
PL-1	
	C
	2007

Deposit the rebar inside aluminum post.

Set a steel fence post along the east side of aluminum post.

THE METES AND BOUNDS SURVEY OF PARCEL 1 IN
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located, 11 ft. east of a north and south barbed wire fence.

Thence **S. 1°05.3' E.**, along the N-S center line of section 20.

- 4.680** The 1/4 section corner of sections 20 and 29, hereinbefore described. This point shall now also function as angle point 6 of parcel 1.

Thence **N. 89°59.3' W.**, between sections 20 and 29.

- 36.878** The corner of sections 19, 20, 29 and 30, hereinbefore described. This point shall now also function as angle point 7 of parcel 1.

Thence **S. 89°45.1' W.**, between sections 19 and 30.

- 39.832** The angle point of sections 19 and 30, hereinbefore described. This point shall now also function as angle point 8 of parcel 1.

Thence **N. 88°58.0' W.**, between sections 19 and 30.

- 2.267** Angle point 1 of parcel 1, identical with the true point for the closing corner of sections 19 and 30, and point of beginning.

The Metes and Bounds Survey of Parcel 2 in
Township 2 South, Range 6 West, Salt Lake Meridian, Utah

The Survey is based upon Parcel 2 of the Warranty Deed filed with the Tooele County recorder's office, dated November 30, 1995, book 409, pages 435-436; Stansbury Investments Associates, Grantor and the United States Of America, Grantee.

Note: Parcel 2 shall hereby consist of lots 1, 5, and 6, and the NE 1/4 of the NW 1/4 of section 29, as depicted on the survey plat. Since the north, east, and west boundaries of parcel 2 have been surveyed hereinbefore, only the south boundary of parcel 2 is surveyed below.

From angle point 1 of parcel 2, on the section line between sections 29 and 30, hereinbefore described.

Thence, **S. 89°59.2' E.**

- 37.257** Angle point 2 of parcel 2, on the N-S center line of section 29, hereinbefore described.
-

THE METES AND BOUNDS SURVEY OF PARCEL 2 IN
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Thence, **N. 1°02.0' W.**, along the N-S centerline of section 29.

0.269 The center N 1/16 section corner of section 29, hereinbefore described.

20.350 The 1/4 section corner of sections 20 and 29, identical with angle point 6, parcel 1, hereinbefore described.

Thence, **N. 89°59.3' W.**, between sections 20 and 29.

36.878 The corner of sections 19, 20, 29, and 30, identical with angle point 7, parcel 1, hereinbefore described.

Thence, **S. 0°00.7' E.**, between sections 29 and 30.

20.077 The N 1/16 section corner of sections 29 and 30, hereinbefore described.

20.346 Angle point 1 of parcel 2, and point of beginning.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Calvert C. Norton	Survey Technician
Adrian Kurip	Survey Technician

CERTIFICATE OF SURVEY

We, Ronald K. Baugh, Supervisory Cadastral Surveyor, and Daniel T. Gillins, Cadastral Surveyor, HEREBY CERTIFY upon honor, that in pursuance of Special Instructions bearing the date of the 23rd day of August, 2007, we have dependently resurveyed a portion of the north boundary of Township 3 South, Range 6 West, dependently resurveyed the east boundary, and a portion of Mineral Survey No. 5615, of Township 2 South, Range 7 West, dependently resurveyed a portion of the subdivisional lines, dependently resurveyed portions of Mineral Survey Nos. 5615 and 5621, subdivided sections 7, 18, 20, and 29, and surveyed the metes-and-bounds survey of parcels 1 and 2, in Township 2 South, Range 6 West, of the Salt Lake Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions of the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 3, 2010

Date

Ronald K. Baugh
(Supervisory Cadastral Surveyor)

February 3, 2010

Date

Daniel T. Gillins
(Survey Technician)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the dependent resurvey of a portion of the north boundary of Township 3 South, Range 6 West, the dependent resurvey of the east boundary, and a portion of Mineral Survey No. 5615, of Township 2 south, Range 7 West, the dependent resurvey of a portion of the subdivisional lines, the dependent resurvey of portions of Mineral Survey Nos. 5615 and 5621, the subdivision of sections 7, 18, 20, and 29, and the metes-and-bounds survey of parcels 1 and 2, in Township 2 South, Range 6 West, having been critically examined and found correct, are hereby approved.

April 15, 2011

Date

Daniel W. Webb
(Chief Cadastral Surveyor for Utah)

TOWNSHIP 2 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1052, dated August 23, 2007.

The direction of the lines was determined by references to true meridians, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods dated May 9, 2001, Version 1.0. Trimble model 5800 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for the project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Geodetic Control was derived from GPS static observations, post processed by the National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS): KENNECOTT1UT2005 CORS ARP, MIDVALE CORS ARP, and RED BUTTE CORS ARP.

The geographic position of the 1/4 section corner of sections 29 and 32, as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: 40°36'22.991" N.,
Longitude: 112°33'06.931" W., N.A.D. 1983,
Network Accuracy = 0.200 meter at 95% confidence.

Note 1: C.L. Heist, surveyor for the General Land Office (G.L.O.) surveyed the east boundary of T. 2 S., R. 7 W., in 1912, setting section corners and 1/4 section corners; the monuments were marked as common to sections of T. 2 S., Rs. 6 and 7 W. At approximately the same time, G.L.O. surveyors J.R. Stewart and R. Gentry were completing the subdivision of T. 2 S., R. 6 W. (from 1912 - 1915). To maintain rectangularity for the section lines in T. 2 S., R. 6 W., Stewart and Gentry set closing section corners referring to sections of the township to the east, and re-marked the section corners set by C.L. Heist to refer to section corners of the township to the west. Stewart and Gentry make no record of establishing 1/4 section corners for the sections of the township to the east, or correcting the marks on the 1/4 section corners set by C.L. Heist to refer to sections of the township to the west only. However, during this survey, a double set of 1/4 section corners set by the G.L.O. were found on the said range line, marked with years 1912 or 1914. One set of 1/4 section corners are marked for sections in T. 2 S., R. 7 W. These monuments were accepted as the 1/4 section corners set by C.L. Heist during his survey of the east boundary of T. 2 S., R. 7 W. Another set of 1/4 section corners were found marked for sections in T. 2 S., R. 6 W. It is believed Stewart and Gentry set these monuments and their records were lost. Both sets of 1/4 section corners are harmoniously related to existing original section corners, have long been recognized as the corners, and are accepted as the original corner positions. These monuments are described herein.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY OF
TOWNSHIP 3 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the North Boundary of
Township 3 South, Range 6 West, Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by J.R. Stewart &
C.L. Heist in 1912

Beginning at the corner of sections 31 and 32 only, Township 2 South, Range 6 West, monumented with an iron post, 3 inches diameter, loosely set, projecting 21 inches above the ground, with brass cap marked as described in the official record of the 1912 survey.

Corner is located under a north and south barbed wire fence and 18 inches north of an east and west barbed wire fence.

S. 89°58.8' W., on the north boundary of section 6.

- 39.954 The 1/4 section corner of sections 6 and 31, determined at the center of a scattered mound of stone, with the 1912 iron post monument lying alongside with brass cap marked as described in the official record of the 1912 survey.

This point will function as an angle point of sections 6 and 31, Townships 2 and 3 South, Range 6 West.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, in a mound of stone, 3 ft. base to top of aluminum cap marked:

T 2 S R 6 W
1/4 S 31
<hr/>
2007

N. 89°57.2' W., beginning new measurement.

- 2.214 The closing corner of Township 2 South, Ranges 6 and 7 West, monumented with an iron post, 3 inches diameter, firmly set, projecting 9 inches above the ground with brass cap marked:

T 2 S T 2 S
R 7 W R 6 W
<u>S 36</u> <u>S 31</u>

1912

A scattered mound of stone bears north, and an east and west dirt road bears south, 88 ft. from corner.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY OF
TOWNSHIP 3 SOUTH, RANGE 6 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

Reestablishment of the Survey Executed by J.R. Stewart
and C.L. Heist in 1912 and the Retracement Executed
by R.C. Yundt in 1937

- 30.478 The corner of Township 3 South, Ranges 6 and 7 West, monumented with an iron post, 3 inches diameter, loosely set, projecting 31 inches above the ground, in a mound of stone, 4 ft. base, 18 inches high, with brass cap marked as described in the official record of the 1912 survey.

Rebuild mound of stone, 4 ft. base, 2 ft. high, around iron post.

Dependent Resurvey of the East Boundary of
Township 2 South, Range 7 West, Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
C.L. Heist in 1912

From the corner of Townships 1 and 2 South, Range 7 West, monumented with an iron post, 1 inch diameter, firmly set, projecting 1 inch above the ground, with brass cap. This monument was set during the 1937 dependent resurvey of the north boundary of Township 2 South, Range 7 West, executed by R.C. Yundt, but is incorrectly marked with the year "1913". Re-mark the year as "1937" so that the brass cap is now marked as described in the official record of the said 1937 resurvey.

Corner is located on a steep, north facing, rocky slope.

S. $0^{\circ}03.7'$ W., on the east boundary of section 1.

- 6.331 The closing corner of Townships 1 and 2 South, Range 6 West, monumented with an iron post, 3 inches diameter, firmly set, 18 inches in the ground, broken at ground surface, with remaining iron post with brass cap lying alongside, marked as described in the official record of the 1912 survey.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, in a collar of stone, 3 ft. base, with aluminum cap marked:

```

      T 1 S
R 7 W | R 6 W
S 36 |
      C | S 31
S 1 C | S 6
      T 2 S
      2007
  
```


DEPENDENT RESURVEY OF THE EAST BOUNDARY OF
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

- 7.240** The 80th 1/16 section corner of section 1, Township 2 South, Range 7 West, monumented with a General Land Office (G.L.O.) iron post, 1 inch diameter, firmly set in a mound of stone, 3 ft. base, 12 inches high, to top of brass cap marked:

T 2 S	
S 1	
1	
8	
R 7 W	
1937	

There is no record of this G.L.O. monument in the official record of the 1937 survey in Township 2 South, Range 7 West, executed by R.C. Yundt. This position is harmoniously related to existing original corners, has long been recognized as the corner, and is accepted as the corner position.

- 46.999** The 1/4 section corner of section 6 only, Township 2 South, Range 6 West, monumented with a G.L.O. iron post, 1 inch diameter, projecting 18 inches above the ground, in a scattered mound of stone, 2 ft. base, with a mound of stone, 3 ft. base, 1 ft. high, 4 links west, and a brass cap marked:

1/4		S 6
1914		

There is no record of this G.L.O. monument in the official record of the 1912-15 survey. This position is harmoniously related to existing original corners, has long been recognized as the corner, and is accepted as the original corner position. See note 1.

Set a steel fence post 3 links south of iron post.

Corner is located on a north and south bench in scattered boulder field.

- 47.310** The 1/4 section corner of section 1 only, monumented with an iron post, 1 inch diameter, firmly set 12 inches in the ground, broken 1 inch below ground surface, in a scattered mound of stone. Did not find the remaining iron post with brass cap.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to bedrock, in a mound of stone, 3 ft. base to top of aluminum cap marked:

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

T 2 S
R 7 W R 6 W
1/4 |
S 1 |
2007

Deposit the 1912 iron post alongside the aluminum post.

S. 0°04.6' W., beginning new measurement.

- 39.727 The closing corner of sections 6 and 7, Township 2 South, Range 6 West, bears east, 0.087 chains distance, monumented with an iron post, 2 inches diameter, firmly set, in a mound of stone, 4 ft. base, 3 ft. high, to top of brass cap marked as described in the official record of the 1912-15 survey.

Set a steel fence post 2 links south of iron post.

Corner is located on jagged rocks, projecting above north slope.

- 40.005 The corner of sections 1 and 12 only, monumented with an iron post, 3 inches diameter, firmly set, in a mound of stone, 4 ft. base, 3 ft. high, to top of brass cap marked as described in the official record of the 1912-15 survey.

Set a steel fence post 3 links west of iron post.

Corner is located on top of large rocks projecting above a north facing slope.

S. 0°03.8' W., on the east boundary of section 12.

- 39.717 The 1/4 section corner of section 7 only, Township 2 South, Range 6 West, monumented with a G.L.O. iron post, 1 inch diameter, firmly set, flush with the ground, with a mound of stone, 3 ft. base, 6 inches high, 2 links west, and a brass cap marked:

1/4 | S 7
1914

There is no record of this G.L.O. monument in the official record of the 1912-15 survey. This position is harmoniously related to existing original corners, has long been recognized as the corner, and is accepted as the original corner position. See note 1.

- 39.998 The 1/4 section corner of section 12 only, monumented with an iron post, 1 inch diameter, firmly set, 14 inches in the ground, broken 2 inches below ground surface, with a mound of stone, 3 ft. base, 6 inches high, 2 links west. Did not find the remaining

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF
TOWNSHIP 2 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

iron post with brass cap.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T 2 S
R 7 W R 6 W
1/4
S 12
2008

Deposit the 1912 iron post alongside the aluminum post.

S. 0°04.2' E., beginning new measurement.

19.813 Point for the S 1/16 section corner of section 7 only, Township 2 South, Range 6 West, not monumented.

39.907 Point for the closing corner of sections 7 and 18, Township 2 South, Range 6 West, at proportionate distance. Found the entire 1914 iron post, lying out of the ground, down the slope.

Re-set the 1914 iron post, 36 inches long, 2 inches diameter, 4 inches in the ground to bedrock, in a mound of stone, 4 ft. base to top of brass cap marked as described in the official record of the 1912-15 survey. Add the marks "2008" to the brass cap.

Corner is located on steep, west-southwest facing slope.

40.198 Point for the corner of sections 12 and 13 only, at proportionate distance. Found the 1912 iron post, 34 inches long, 3 inches diameter, broken and lying out of the ground, down the slope, with brass cap marked as described in the official record of the 1912-15 survey. Point falls on west face of outcropping limestone rock.

Set a rebar, 8 inches long, 3/4 inches diameter, drilled and cemented 4 inches into solid rock, with aluminum cap marked:

T 2 S
R 7 W R 6 W
S 12
S 13
S 18
2008

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, 4 links northeast of corner.

Corner is located on steep, west-southwest facing slope.
